

## CHAPTER

## 8



## Work, Power and Energy

**Work Done by constant Force**

$$W = \vec{F} \cdot \vec{S}$$

**Work Done by Multiple Forces**

$$\Sigma \vec{F} = \vec{F}_1 + \vec{F}_2 + \vec{F}_3 + \dots$$

$$W = [\Sigma \vec{F}] \cdot \vec{S}$$

$$W = \vec{F}_1 \cdot \vec{S} + \vec{F}_2 \cdot \vec{S} + \vec{F}_3 \cdot \vec{S} + \dots \text{ or } W = W_1 + W_2 + W_3 + \dots$$

**Work Done by Variable Force**

$$W = \int dW = \int \vec{F} \cdot d\vec{s}$$

Area under the force and displacement curve gives work done.

**Important cases:**

(i) The force is perpendicular to velocity at all times. The work done in this case is zero. e.g., :

(a) A particle attached to a string whose other end is attached to a fixed point. The work done by tension in the string is zero.

(b) A body moving on a fixed surface. The work done by normal reaction is zero in this case.

(ii) Work done by gravity on a body near the surface of earth

$$= -mg(h_f - h_i)$$

$$= -mg \times \text{increase in height}$$

(iii) Work done by friction on a block moving on a fixed surface

$$= -\mu_k \int N(s) ds$$

$$= -\mu_k N \times \text{distance travelled (if } N \text{ is constant).}$$

Here  $N$  is the normal reaction between the block and the surface on which it is moving.

(iv) Work done by a spring on a block

$$= -\frac{1}{2}k(x_f^2 - x_i^2)$$

where  $x_i$  and  $x_f$  refer to the initial and final elongation or compression of the spring.

**Relation between Momentum and Kinetic Energy**

$$K = \frac{P^2}{2m} \text{ and } P = \sqrt{2mK}$$

$P$  = linear momentum

**Potential Energy**

$$\int_{U_1}^{U_2} dU = - \int_{r_1}^{r_2} \vec{F} \cdot d\vec{r}$$

$$\text{i.e., } U_f - U_i = - \int_{r_i}^{r_f} \vec{F} \cdot d\vec{r} = -W_{\text{Conservative}}$$

**Conservative Forces**

$$\vec{F} = -\frac{dU}{dr} \hat{r}$$

$$\vec{F} = -\frac{\partial U}{\partial x} \hat{i} - \frac{\partial U}{\partial y} \hat{j} - \frac{\partial U}{\partial z} \hat{k}$$

**Equilibrium Conditions****Stable Equilibrium**

$$F(r) = -\frac{dU}{dr} = 0, \text{ and } \frac{dF}{dr} < 0; \text{ or } \frac{d^2U}{dr^2} > 0$$

**Unstable Equilibrium**

$$F(r) = -\frac{dU}{dr} = 0; \text{ and } \frac{dF}{dr} > 0; \text{ or } \frac{d^2U}{dr^2} < 0$$

**Neutral Equilibrium**

$$F(r) = -\frac{dU}{dr} = 0; \text{ and } \frac{dF}{dr} = 0; \text{ or } \frac{d^2U}{dr^2} = 0$$

**Work-Energy Theorem for a Particle**

$$W_{\text{Net}} = \frac{1}{2}mv_f^2 - \frac{1}{2}mv_i^2$$

**Work-Energy Theorem for a System**

$$\Delta K + \Delta U = W_{\text{ext}} + W_{\text{int-NC}}$$

**Law of Conservation of Mechanical Energy**

If the net external force acting on a system is zero and internal non-conservative forces absent, then the mechanical energy is conserved.

$$K_f + U_f = K_i + U_i$$

**Power**

The average power delivered by an agent is given by

$$P_{\text{avg}} = \frac{W}{t}$$

$$P = \frac{d\vec{F} \cdot \vec{S}}{dt} = \vec{F} \cdot \frac{d\vec{S}}{dt} = \vec{F} \cdot \vec{v}$$